

D
A
T
A
S
H
E
E
T

Laminated Glass Product Data Sheet

Precision Glass Industries is a Houston-based glass fabrication company, with a focus on tempered, heavy fabricated glass, laminated, back-painted, and commercial insulated glass. The backbone of the company is our ability to stay focused on overall product quality, 100% On-Time-Delivery, and shortened lead times. These attributes keep us grounded and in tune with our customers' needs, allowing for complete customer satisfaction.

Precision Glass Industries fabricates glass in compliance with industry standards including ANSI Z-97 of the American National Standards Institute. In addition, the Consumer Product Safety Commission (CPSC) 16 CFR 1201 wherein the local and national building codes recognize it as the standard that must be met for glass products used in windows.

Laminated Glass

All Laminated glass fabricated at Precision Glass Industries complies with ASTM C 1172 for kinds of laminated glass indicated and other requirements specified.

Interlayer of 0.030", 0.060" and 0.090" or ionoplast sheet interlayer material with a proven record of no tendency to bubble, discolor, or lose physical and mechanical properties after laminating glass lites and installation. Precision Glass Industries is also recognized as a laminator of Kuraray brand interlayers for Sentry Glass Plus (SGP) as required by the Miami-Dade County Department of Regulatory & Economic Resources thereby permitting and recognizing us as a laminator to supply laminated glass into the hurricane markets. Precision Glass Industries offers diverse range of products to our customers including the following:

SentryGlas® (Clear and White) Interlayers – No. 17-0808.02 SentryGlas® Xtra™ (SGXTM) Clear Glass Interlayer – No. 18-0725.1.

At Precision Glass Industries we follow stringent guidelines for testing tempered products of our facility and as per recommendations defined by the glass industry. Guardian and AGC are the current brands of glass manufacturers carried by Precision.

Evaluation Criteria used for Laminated Glass:
ANSI Z-97:

- No fracture at specified Class drop height
- If fracture occurs at the specified Class drop height, the ten largest crack free particles shall not weigh more than 10 square inches of the glass tested.

CPSC 16 CFR 1201:

- The ten largest crack free particles shall not weigh more than 10 square inches of the glass tested
- If no fracture occurs from impact test, the glass is to be broken using center punch test.

Disclaimer:

Tempered glass may contain nickel sulfide stones or more commonly known as inclusions and their presence does not render the glass defective. Spontaneous glass breakage is a phenomenon by which toughened glass (or tempered) may spontaneously break without any apparent reason; most common causes are chipped edges, surface scratches and installation quality. This could occur years after the installation. Customer understands and accepts that glass may be susceptible to breakage and that customer will not hold Precision Glass Industries, or any of its authorized representatives responsible for commercial loss, or any direct or indirect consequential damages, including but not limited to the associated costs of removal or installation including labor costs of the product, defective or otherwise and agrees to indemnify and hold Precision Glass Industries harmless from any such loss, damage or injury brought by their customers or third parties. Please direct all related questions to info@precisionglassindustries.com

PRECISION
GLASS INDUSTRIES

